

StatSpin[®] Express 3

PRIMARY TUBE CENTRIFUGE

Achieve Faster Turnaround Times and Greater Productivity

The StatSpin Express 3 provides faster turnaround time and greater productivity for your laboratory. Place it next to any STAT analyzer and serum or plasma is ready in just minutes.

With only 3 settings it is simple to use. Just select the 2, 3 or 5 minute button and press start. No fumbling with settings or the need to readjust the speed. For safety, the lid remains locked until the rotor comes to a complete stop. The unit beeps when it is done spinning.

Samples can be processed as they arrive in the lab; no need for batching, no unproductive time spent waiting for the centrifuge ...you'll have results in minutes. Now you can process as many as 8 samples at once for higher throughput.



The Express 3 comes with adapters for 5 and 10 mL tubes.



The StatSpin Express 3 holds 8 tubes up to 10 mL.

StatSpin Express 3 is Ideal for:

- Rapid plasma for coagulation testing
- Sample prep for STAT chemistry
- Cardiac profiles in the ER
- Anywhere rapid serum or plasma is needed

High Quality Results

In just 2 minutes, the Express 3 can produce serum or plasma equal to tubes spun for 7-10 minutes in conventional clinical centrifuges.

StatSpin Express 3 : Small, Fast, Powerful

StatSpin Express 3 is UL and CE marked. Universal power input works off any AC electrical power from 100-240V. Suitable for worldwide locations.

The StatSpin Express 3 is powerful. The rugged brushless motor is maintenance-free. StatSpin provides a comprehensive 2-year warranty.

The StatSpin Express 3 comes with adaptors for 5 and 10 mL tubes. Adaptors are also available for other tube sizes.



System Specifications:

Dimensions	Height	7.1 inches/18.0 cm
	Width	10.5 inches/26.7 cm
	Depth	10.0 inches/25.4 cm
	Weight	9.5 lbs (4.3 kg)
Acceleration Time	<25 seconds to 95 % of speed	
Deceleration Time	< 30 seconds	
Cycle Times/Speed/RCF	2 minutes	7200 rpm/4400 xg (+/-5%)
	3 minutes	7200 rpm/4440 xg (+/-5%)
	5 minutes	5600 rpm/2685 xg (+/-5%)
Tube Sizes	Accepts blood tubes 1.5-10mL	
Power Requirements	100 to 240V, 50/60 Hz, 3 amp	
Warranty	2 Years	

StatSpin Express 3 Ordering Information

Product #	Description
SSX3	StatSpin Express 3 for 100-240V, 50/60 Hz. Includes 8 place rotor, removable bowl liner, eight 5 mL inserts, eight 10 mL inserts and power cord.

Iris[®]
Sample Processing

60 Glacier Drive
Westwood, MA 02090
Tel: 781.551.0100
Fax: 781.551.0036
800.782.8774
www.proiris.com

